

11-13-00

A

PTO/SB/05 (08-00)

Please type a plus sign (+) inside this box → ☐

Approved for use through 10/31/2002. OMB 0651-0052

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.	MS160275.1
First Inventor	Bourke-Dunphy, et al.
Title	LOCATION-BASED SCENARIOS TO
Express Mail Label No.	EF185629287US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☐ Applicant claims small entity status.
See 37 CFR 1.27.
3. ☒ Specification [Total Pages 22]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross Reference to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to sequence listing, a table, or a computer program listing appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
4. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 9]
5. Oath or Declaration [Total Pages 2]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63 (d))
(for continuation/divisional with Box 17 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b)
6. ☐ Application Data Sheet. See 37 CFR 1.76

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

7. ☐ CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix)
8. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Form (CRF)
 - b. Specification Sequence Listing on:
 - i. ☐ CD-ROM or CD-R (2 copies); or
 - ii. ☐ paper
 - c. ☐ Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

9. ☒ Assignment Papers (cover sheet & document(s))
10. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
11. ☐ English Translation Document (if applicable)
12. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
13. ☐ Preliminary Amendment
14. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☒ Other: Express Mail Certificate

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP)

of prior application No. _____ / _____

Prior application information

Examiner _____

Group / Art Unit _____

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

18. CORRESPONDENCE ADDRESS☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☒ Correspondence address below

Name	Himanshu S. Amin				
Address	Amin, Eschweiler & Turocy, LLP 24th Floor, National City Center, 1900 East Ninth Street				
City	Cleveland	State	Ohio	Zip Code	44114
Country		Telephone	216-696-8730	Fax	216-696-8731

Name (Print/Type)	Himanshu S. Amin	Registration No. (Attorney/Agent)	40,894
Signature			Date November 10, 2000

Burden Hour Statement This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number

**FEE TRANSMITTAL
for FY 2001**

Patent fees are subject to annual revision

TOTAL AMOUNT OF PAYMENT (\$) 848.00**Complete if Known**

Application Number	
Filing Date	Herewith
First Named Inventor	Erin M. Bourke-Dunphy, et al.
Examiner Name	
Group Art Unit	
Attorney Docket No.	MS160275.1

METHOD OF PAYMENT

1. ☒ The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to
- Deposit Account Number **50-1063**
- Deposit Account Name **Amin, Eschweiler & Turocy, LLP**
- ☒ Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17
- ☐ Applicant claims small entity status. See 37 CFR 1.27
2. ☒ **Payment Enclosed:**
- ☒ Check ☐ Credit card ☐ Money Order ☐ Other

FEE CALCULATION**1. BASIC FILING FEE**

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
101 710	201 355	Utility filing fee	710
106 320	206 160	Design filing fee	
107 490	207 245	Plant filing fee	
108 710	208 355	Reissue filing fee	
114 150	214 75	Provisional filing fee	

SUBTOTAL (1) (\$) 710.00**2. EXTRA CLAIM FEES**

Total Claims **21** - 20** = **1** X **18** = **18**

Independent Claims **4** - 3** = **1** X **80** = **80**

Multiple Dependent **0** = **0**

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description
103 18	203 9	Claims in excess of 20
102 80	202 40	Independent claims in excess of 3
104 270	204 135	Multiple dependent claim, if not paid
109 80	209 40	** Reissue independent claims over original patent
110 18	210 9	** Reissue claims in excess of 20 and over original patent

SUBTOTAL (2) (\$) 98.00

**or number previously paid, if greater, For Reissues, see above

FEE CALCULATION (continued)**3. ADDITIONAL FEES**

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
105 130	205 65	Surcharge - late filing fee or oath	
127 50	227 25	Surcharge - late provisional filing fee or cover sheet	
139 130	139 130	Non-English specification	
147 2,520	147 2,520	For filing a request for ex parte reexamination	
112 920*	112 920*	Requesting publication of SIR prior to Examiner action	
113 1,840*	113 1,840*	Requesting publication of SIR after Examiner action	
115 110	215 55	Extension for reply within first month	
116 390	216 195	Extension for reply within second month	
117 890	217 445	Extension for reply within third month	
118 1,390	218 695	Extension for reply within fourth month	
128 1,890	228 945	Extension for reply within fifth month	
119 310	219 155	Notice of Appeal	
120 310	220 155	Filing a brief in support of an appeal	
121 270	221 135	Request for oral hearing	
138 1,510	138 1,510	Petition to institute a public use proceeding	
140 110	240 55	Petition to revive - unavoidable	
141 1,240	241 620	Petition to revive - unintentional	
142 1,240	242 620	Utility issue fee (or reissue)	
143 440	243 220	Design issue fee	
144 600	244 300	Plant issue fee	
122 130	122 130	Petitions to the Commissioner	
123 50	123 50	Petitions related to provisional applications	
126 240	126 240	Submission of Information Disclosure Stmt	
581 40	581 40	Recording each patent assignment per property (times number of properties)	40.00
146 710	246 355	Filing a submission after final rejection (37 CFR § 1.129(a))	
149 710	249 355	For each additional invention to be examined (37 CFR § 1.129(b))	
179 710	279 355	Request for Continued Examination (RCE)	
169 900	169 900	Request for expedited examination of a design application	

Other fee (specify) _____

*Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$) 40.00**SUBMITTED BY**

Name (Print/Type)	Himanshu S. Amin	Registration No (Attorney/Agent)	40,984	Telephone	216-696-8730
Signature		Date	11/10/00		

Complete (if applicable)

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement. This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Atty. Docket No. MS160275.1

LOCATION-BASED SCENARIOS TO
FACILITATE SELECTION OF SYSTEM
CONFIGURATION

by

Erin M. Bourke-Dunphy and Jeff A. Zimniewicz

CERTIFICATION

I hereby certify that the attached patent application (along with any other paper referred to as being attached or enclosed) is being deposited with the United States Postal Service on this date November 10, 2000, in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number EF185629287US addressed to the: Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

Himanshu S. Amin

(Typed or Printed Name of Person Mailing Paper)



(Signature of Person Mailing Paper)

**Title: LOCATION-BASED SCENARIOS TO FACILITATE SELECTION
OF SYSTEM CONFIGURATION**

Technical Field

5 The present invention relates to computer programming and, more particularly, to a system and method to facilitate configuration and/or setup of a software system based on its installation location.

Background

10 Software applications and/or services are commonly offered to consumers in the form of grouped packages or suites, in which two or more such applications are provided. A suite is generally provided at a lower cost than if the individual applications included therein were purchased separately. In addition, a software suite typically includes an assortment of related and/or interoperable application or service
15 components targeted to satisfy the software needs of a particular type of customer, such as small businesses or other types of organizations. Different application suites may thus be provided to satisfy various market needs, where certain segments of software consumers commonly require more than one application or service.

20 It is common to selectively install different applications of a suite onto one or more interconnected computers. For example, an organization may include several servers physically located at different locations, *e.g.*, one server at a corporate central office, with additional servers located at remote locations. The particular application and/or services that should be installed at each server in the organization may vary as a function of the type of organization and the performance objectives of the
25 administrator that implements the installation.

30 During one type software installation, a user may be presented with a list that provides several functional descriptions of different installation scenarios from which the user is to select. However, the choices presented may fail to provide a suitable functional definition for the installation based on the customer's objectives as to how
35 the software is to be utilized in the organization. For example, the computer onto which the software is being installed may fall within the functional definitions associated with more than one of the available choices. As a result, a user may be confused as to the appropriate selection for the installation. Moreover, if the user were to select an incorrect option for the installation, one or more components that the user may need at that computer may not be made available for installation, which

could require reinstallation. Therefore, it is common for a user to exit a functionality-based setup process and proceed with a custom installation. However, a custom installation typically provides little or no guidance as to what components should be selected for a given type of installation.

5 Other types of software may provide a limited number of installation choices, such as to implement a complete installation or a minimal installation. The complete installation usually installs all available components onto the user's computer, with little or no tuning to the user's situation. A minimal installation usually installs only those components that are necessary for the software to function properly. Both of
10 these options lack adequate tuning of the installation according to where the software is being installed.

 Therefore, it is desirable to provide a system and method to help configure a software system during an installation process according to the location of the computer.

15

Summary

 The following presents a simplified summary of the invention in order to provide a basic understanding of some aspects of the invention. This summary is not an extensive overview of the invention. It is intended to neither identify key or
20 critical elements of the invention nor delineate the scope of the invention. Its sole purpose is to present some concepts of the invention in a simplified form as a prelude to the more detailed description that is presented later.

 One aspect of the present invention provides a system and method to facilitate selection and/or configuration of software components during installation of a
25 software system. Information is acquired indicative of a computer location onto which application components are to be installed. For example, a graphical user interface may provide a discrete number of selections describing two or more location-based scenarios from which a user may select an appropriate response. Alternatively, the system location information may be acquired from a system registry
30 or other data storage.

 The software system is configured as a function of the acquired location information. The configuration characteristics, which may include system infrastructure and/or functionality of the software system, further may

Another aspect of the present invention provides a method for configuring a software system. The method includes selecting a scenario based on a location of where the software system is to be installed and determining a configuration for software system the based on the selected scenario. In accordance with an aspect of the present invention, the method may be implemented as computer-executable instructions in a computer-readable medium.

15

20

25

Fig. 2 is a functional block diagram of a system to facilitate configuring a software system in accordance with the present invention;

30

Fig. 4 is an example of a user interface for identifying a type of server in accordance with the present invention;

Fig. 5 is another example of a graphical user interface for selecting an installation location in accordance with the present invention;

Fig. 6 is another example of a user interface for identifying a type of server in accordance with the present invention;

5 Fig. 7 is an example of a user interface for selecting components in accordance with the present invention;

Fig. 8 is an example of a operating environment in which the present invention may be implemented; and

10 Fig. 9 is a flow diagram illustrating a methodology for configuring a software system in accordance with the present invention.

Description of the Invention

15 The present invention relates to a system and method to facilitate selection and/or configuration of software components during a setup process associated with installation of a plurality of software components. Information is acquired indicative of a location onto which the components are to be installed. The location information is employed to configure the software components, such as by setting at least some of the components as default components.

20 Fig. 1 is a diagrammatic representation of a system 10 that may be utilized to facilitate configuration of application and/or service components of a software system in accordance with an aspect of the present invention. The system 10 includes a setup engine 12 programmed to configure a software system for installation onto a computer. The setup engine 12 receives location data indicative of a location for the computer, such as a server, onto which a software system is being installed. The
25 location information may be entered by a user at an appropriate user interface and/or be determined from data stored in the computer or a directory service (*e.g.*, a distributed directory) of an associated network domain to which the computer belongs. For example, the setup engine 12 may collect selected data from a system registry and, upon application of a suitable algorithm, deduce an indication of the
30 computer location sufficient to drive the setup process in accordance with an aspect of the present invention.

The software system being installed includes a plurality of components, such as may be server-based applications or Web-based services, although the system 10

may be employed to facilitate configuration of other types of software systems. The setup engine 12 determines a desirable component configuration 14 based on the location data. The determined component configuration 14, for example, may be cached to memory and presented to a user in the form of a graphical user interface (GUI). The user may, in turn, accept the recommended (*e.g.*, default) components for installation or customize the components, as desired. The component configuration 14 further includes corresponding configuration information for each of the selected components, in which the functionality of each selected component may further be tuned based on the location data.

Fig. 2 illustrates another example of a setup engine 50 in accordance with an aspect of the present invention. In this example, the setup engine 50 includes an interface 52, such a may be a graphical user interface. The interface 52 includes a location interface component 54 that acquires information about the location of a computer onto which a software system is being installed. The location interface component 54, for example, includes a GUI that presents two (or more) selectable options describing possible location scenarios for the computer onto which a software system 56 is being installed. The system 56, for example, is packaged to include components that may be used for a variety of different system environments (*e.g.*, networked or stand-alone computer environments), all of which may be represented by the location interface component 54 as different selectable location scenarios.

By way of illustration, assume that the software system 56 includes a server system having plurality of server components. The components may include a main server component, a database component, a management component, an email component, a fax component, a hosting component, a firewall component, etc. Those skilled in the art will understand and appreciate other possible components that may be desirable to install in connection with a server system, all of which of considered as being within the scope of the present invention. Table I provides a more detailed example of high-level components that could be installed as part of a server system in accordance with an aspect of the present invention.

TABLE I		
SERVER SYSTEM		
	Administration	
		Consoles
		Wizards
		Snap-Ins
		Remote Management
		Web Administrator
		Active Directory Configuration
		System User Upgrade
		System Console Upgrade
		System Console Upgrade
	Monitoring	
		Health Monitoring
		Server Status View
		Server Status Report
		Monitoring Troubleshooting
	Connectivity	
		ICW
		POP3 Connector
	Client Setup	
		Set Up Computer Wizard
		Internet Browser
		Messaging Reader
		IME
		Proxy Client
		Modem Sharing Client
		Fax Client
		Host Integration Client
		OS Updates
	Documentation	
		Online Guide
		Intranet
Optional Components		
	Internet Information Server	
		Internet Information Server Snap-In
		Internet Information Server Documentation
		NNTP
		SMTP
		World Wide Web Service

TABLE I Continued	
Database System	
	Server Components
	Management Tools
	Client Connectivity
	Books Online
Proxy	
Fax	
Modem Sharing	
Computer Management	
Host Integration Server	
Messaging and Collaboration System	
	Messaging and Collaboration
	System Management Tools

Those skilled in the art will understand and appreciate that the foregoing list of server components is for purposes of illustration, and that various different components could be utilized in accordance with an aspect of the present invention. For example, it may be desirable to install a different set of components depending on where the server system is being installed and the particular server system being installed. Moreover, different functionality of certain components by be desired depending upon where the system is being installed.

The setup engine 50 is programmed, in accordance with an aspect of the present invention, to determine configuration data 58 for the software system 56 based on the location information acquired by the location interface component 54. The configuration data 58, for example, may provide default selection data 60, which identifies available components from the software system 56 that have been selected as a function of the location information. The default selection data 60 may contain a list of recommended components for installing at the computer having location characteristics identified by the location interface component 54. The default selection data 60 is provided to a component selection interface element 62. In this way, a list of the default components of the software system 56 may be displayed to a user. The user may then employ the component selection interface 62 to accept some, none, or all of the default components as well as to select other components for installation. That is, the component selection interface 62 provides recommended

components for installation based on the location scenario being implemented, but it also is customizable.

The component selection interface 62 provides the user's component selections to a component function element 64. The component function element 64 may configure one or more of the selected components according to the configuration data and the location information. As a result, selected components may be configured to provide a corresponding functionality, which has been tuned according to the location where the software is being installed (*e.g.*, based on the location scenario).

Figs. 3-7 illustrates examples of graphical user interfaces (GUIs) that may be utilized to help configure a software system in accordance with an aspect of the present invention. Fig. 3 illustrates a GUI 100 for selecting a computer (*e.g.*, a server) location onto which an associated software system is being installed in accordance with an aspect of the present invention. In this example, two location scenarios are presented as options for installation, although it is to be appreciated that any number of location scenarios could be utilized as possible installation locations in accordance with an aspect of the present invention.

By way of illustration, a first selectable user interface element 104 is associated with the first installation location scenario, namely, a central server location. The user interface element 104 may be selected where a user desires to employ the computer as part of the main infrastructure for an organization. A second user interface element 106 is associated with an alternative installation location. In particular, the second user interface element 106 may be selected where the computer is to be added to an existing domain structure and configured to connect to a central server. In this example, the central server scenario has been selected. An adjacent window 108 displays a graphical example of a computer infrastructure corresponding to the selected user interface element 104.

The selected user interface element 104 results in a recommended configuration for the software system (*e.g.*, a server system) being implemented. That is, the configuration of the associated software system is tuned according to the particular location scenario selected *via* the GUI 100.

If a user desires additional information concerning the location scenarios presented by the GUI 100, a user may select a MORE INFORMATION action button

110. The action button 110, for example, is associated with a pop-up window that may display additional information associated with the location scenario options 104 and 106. The GUI 100 also includes other action buttons, generally indicated at 112, for navigating a setup process of which the GUI is part. In particular, after selecting a
5 desired installation location scenario, a user may select a NEXT action button 114 for advancing to another GUI screen associated with the setup process. In response to selecting the NEXT action button 114, the setup process (or an associated component thereof) determines a configuration for the software system as a function of the user-selected location scenario.

10 Fig. 4 illustrates an example of a GUI 150 that may be provided for further configuring the software system. In this example, the software system corresponds to a server and the GUI 150 allows a user to specify the type of server. In particular, the GUI 150 includes selectable user interface elements 152, 154, and 156 for setting the central server as a first domain controller, an additional domain controller, or a
15 member server, respectively. It is to be appreciated that, in accordance with an aspect of the present invention, the GUI 150 may be provided in response to selecting the central server location scenario with the GUI 100 and then activating the NEXT button 114 of Fig. 3. The GUI 150 includes additional action buttons 158 for navigating through the setup screens of the setup process.

20 Fig. 5 illustrates another example of a GUI 200 for selecting a computer location scenario where a software system is being installed. The GUI 200 is similar to the GUI 100 of Fig. 3, but corresponds to a situation where a different location scenario has been selected. In particular, the GUI 200 includes first and second selectable user interface elements 204 and 206 respectively associated with different
25 installation location scenarios. In this example, the branch office server scenario has been selected. An adjacent window 208 displays a graphical example of a computer infrastructure corresponding to the selected user interface element 206, namely a typical infrastructure for a situation where a server is implemented at a branch office location. The GUI 200 includes a MORE INFORMATION button 210 for obtaining
30 additional details concerning characteristics of the location where the software is being installed. Other action buttons 212 also are provided for general navigation of GUIs associated with the setup process.

Upon selecting the branch office server location interface element 206 and selecting a NEXT action button 214, the setup process may provide a GUI 220, such as shown in Fig. 6. In Fig. 6, the GUI 220 includes user interface elements 222 and 224 for specifying a type of server the branch office server where the software system
 5 (e.g., a server) is being installed. It is to be appreciated that the server type options presented in this example (e.g., a branch office server) differ from those available where a central server location scenario is selected. That is, configuration options may vary as a function of the selected location scenario. In particular, the user interface element 222 corresponds to selecting the server to be a member server of an
 10 existing domain and user interface element 224 is for selecting the server to be an additional domain controller in an existing domain. Action buttons 226 also are provided for navigating through the setup process.

After the server location has been selected, such as based on the two (or more) available location scenarios, such as shown and described with respect to Figs. 3 and
 15 5, a user is provided with a list of components for recommended installation. In accordance with an aspect of the present invention, the list of components includes default components determined as a function of the selected location scenario (e.g., central server or branch office server). The default components may be automatically selected for installation so as to provide desired functionality associated with the
 20 selected location scenario. The user may customize the setup, such as by deselecting one or more of the default components and/or by selecting other available components to be installed. Moreover, upon selecting components for installation, the selected components further may be tuned based on the selected location scenario.

By way of illustration, Fig. 7 depicts a component selection GUI 250, such as
 25 may be provided to the user for selecting which components are to be installed in accordance with an aspect of the present invention. The GUI 250 includes an ACTION user interface element 252. The ACTION user interface element 252 may be employed to select a desired action to perform with respect to each available component. Each interface element 252 may map to an associated component user
 30 interface element 254 for indicating what action is to be performed with respect to an associated component (e.g., whether or not the component is selected to be installed). The user interface element 254, for example, may include a drop down menu for displaying subcomponents of the respective components. In this way, a hierarchy of

the available components and subcomponents may be shown to the user, from which a user may selectively install each component and/or subcomponent. A dependency manager (not shown) further may be associated with the setup process to help ensure that necessary components and subcomponents are installed. As mentioned above, corresponding components (and associated subcomponents thereof) may be selected for default installation according to the selected location scenario. A user may customize the installation procedure by employing an associated ACTION user interface element 252 to deselect default components so as not to be installed and/or to select other non-default components so as to be installed.

In order to assist a user interact with the GUI 250, the user may select a MORE INFORMATION action button 256. Additionally or alternatively, the MORE INFORMATION action button may be associated with a pop-up window, which may be interactive and displays information about a selected component or subcomponent. A user also may select a BACK action button 258 to return to a previous GUI screen or a cancel button 260 to cancel the current setup and/or installation process.

Once a user is satisfied with the components selected for installation, the user may employ a NEXT action button 262. In response to selecting the NEXT button 262, the associated setup process, in turn, may configure (or tune) particular functionality associated with one or more components and/or subcomponents based on the selected location scenario. In this way, components and/or subcomponents may be configured to have favorable operating characteristics according to where the software system is being installed.

It will be appreciated that the foregoing approach is in contrast to controlling installation of components based on a functionality, as historically has been provided. When a user selects one or more functions to implement with a conventional software system, for example, almost no assumptions may be made about the configuration of the computer because it is uncertain as to where the software system is being installed. Therefore, by utilizing functionality to determine what components to install, a user is provided with preselected components to be installed, which usually cannot be further customized. Moreover, the selected functionality may not adequately correspond to the actual implementation for the software system. Consequently, conventional installation options may not be adequately helpful and may result in a user performing a complete custom installation. By performing a

complete installation of all components, the setup process fails to facilitate selections suited for a particular installation.

A system implemented in accordance with the present invention facilitates setup and/or installation of software components by configuring default components to install for a given installation for a selected location scenario. Moreover, the particular functionality of components that have been selected to be installed may be tuned based on the selected location scenario.

With reference to Fig. 8, an exemplary system environment 300 for implementing the various aspects of the invention includes a computer 302, such as a server. The computer 302 includes a processing unit 304, a system memory 306, and a system bus 308 that couples various system components including the system memory to the processing unit 304. The processing unit 304 may be any of various commercially available processors, including but not limited to Intel x86, PENTIUM and compatible microprocessors from Intel and others, including Cyrix, AMD and Nexgen; ALPHA microprocessors from Digital; MIPS microprocessors from MIPS Technology, NEC, IDT, Siemens, and others; and the POWERPC microprocessors from IBM and Motorola. Dual microprocessors and other multi-processor architectures also may be used as the processing unit 304.

The system bus 308 may be any of several types of bus structure including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of conventional bus architectures such as PCI, VESA, Microchannel, ISA, and EISA, to name a few. The system memory includes read only memory (ROM) 310 and random access memory (RAM) 312. A basic input/output system (BIOS), containing the basic routines that help to transfer information between elements within the computer 302, such as during start-up, is stored in ROM 310.

The computer 302 also may include, for example, a hard disk drive 314, a magnetic disk drive 316, *e.g.*, to read from or write to a removable disk 318, and an optical disk drive 320, *e.g.*, for reading from or writing to a CD-ROM disk 322 or other optical media. The hard disk drive 314, magnetic disk drive 316, and optical disk drive 320 are connected to the system bus 308 by a hard disk drive interface 324, a magnetic disk drive interface 326, and an optical drive interface 328, respectively. The drives and their associated computer-readable media provide nonvolatile storage of data, data structures, computer-executable instructions, etc. for the computer 302.

Although the description of computer-readable media above refers to a hard disk, a removable magnetic disk and a CD, it should be appreciated by those skilled in the art that other types of media which are readable by a computer, such as magnetic cassettes, flash memory cards, digital video disks, Bernoulli cartridges, and the like, may also be used in the exemplary operating environment 300, and further that any such media may contain computer-executable instructions for performing the methods of the present invention.

A number of program modules may be stored in the drives and RAM 312, including an operating system 330, one or more application programs 332, other program modules 334, and program data 336. The operating system 330 in the illustrated computer is, for example, one of the MICROSOFT WINDOWS® operating systems, which are available from Microsoft Corporation. It is to be appreciated, however, that the present invention may be implemented with other operating systems or combinations of operating systems.

A user may enter commands and information into the computer 302 through one or more user input devices, such as a keyboard 338 and a pointing device (e.g., a mouse 340). Other input devices (not shown) may include a microphone, a joystick, a game pad, a satellite dish, a scanner, or the like. These and other input devices may be connected to the processing unit 304 through a serial port interface 342 that is coupled to the system bus 308, although such devices may be connected by other interfaces, such as a parallel port, a game port, a universal serial bus (USB), etc. A monitor 344 or other type of display device is also connected to the system bus 308 via an interface, such as a video adapter 346. In addition to the monitor 344, the computer 302 may include other peripheral output devices (not shown), such as speakers, printers, etc.

As mentioned above, the computer 302 may operate in a networked environment using logical connections to one or more other computers 360, such as may form part of a common network domain. The remote computer 360 may be a workstation, a server computer, a router, a peer device or other common network node, and typically includes many or all of the elements described relative to the computer 302. The logical connections depicted in Fig. 8 may include a local area network (LAN) 364 and a wide area network (WAN) 366. Such networking

environments are commonplace in offices, enterprise-wide computer networks, intranets and the Internet.

When used in a LAN networking environment, the computer 302 is connected to the local network 364 through a network interface or adapter 368. When used in a
5 WAN networking environment, the computer 302 typically includes a modem 370, or is connected to a communications server on the LAN, or has other means for establishing communications over the WAN 366, such as the Internet. The modem 370, which may be internal or external, is connected to the system bus 308 *via* the serial port interface 342 (*e.g.*, for communications over POTS). The modem
10 alternatively may be connected to the system bus 308 *via* the network interface or adapter 368 (*e.g.*, for communication over DSL, cable, satellite, etc.). In a networked environment, program modules depicted relative to the computer 302, or portions thereof, may be stored in the remote memory storage device. It will be appreciated that the network connections shown are exemplary and other means of establishing a
15 communications link between the computers 302 and 360 may be used.

In accordance with the practices of persons skilled in the art of computer programming, the present invention has been described with reference to acts and symbolic representations of operations that are performed by a computer, such as the computer 302 or remote computer 360, unless otherwise indicated. Such acts and
20 operations are sometimes referred to as being computer-executed. It will be appreciated that the acts and symbolically represented operations include the manipulation by the processing unit 304 of electrical signals representing data bits which causes a resulting transformation or reduction of the electrical signal representation, and the maintenance of data bits at memory locations in the memory
25 system (including the system memory 306, hard drive 314, floppy disks 318, CD-ROM 322) to thereby reconfigure or otherwise alter the computer system's operation, as well as other processing of signals. The memory locations where such data bits are maintained are physical locations that have particular electrical, magnetic, or optical properties corresponding to the data bits.

30 In view of the foregoing structural, functional, and graphical features described above, a methodology in accordance with various aspects of the present invention will be better appreciated with reference to Fig. 9. While, for purposes of simplicity of explanation, the methodology of Fig. 9 is shown and described as a

series of steps, it is to be understood and appreciated that the present invention is not limited by the order of steps, as some steps may, in accordance with the present invention, occur in different orders and/or concurrently with other steps from that shown and described herein. Moreover, not all illustrated steps may be required to
5 implement a methodology in accordance with an aspect the present invention.

The process begins at step 400, such as in response to activating a setup and/or installation process for a software system having a plurality of application and/or service components. From step 400, the process proceeds to step 402 in which location information is acquired. For example, the location information may be
10 acquired in response to a user manually selecting one of two or more location scenarios that describe possible installation locations. Alternatively or additionally, information may be read from system memory (*e.g.*, a registry), from a distributed directory of a domain to which the computer is connected, and/or the information may be sensed from the network configuration. The information may be processed to
15 deduce the location information for the computer where the software system is being installed.

The location information, for example, may correspond to one of a predetermined number of location scenarios where a user may desire to install the software system. By way of further illustration, when the software corresponds to a
20 server system, one location scenario may correspond to a central server and a second scenario may correspond to a branch office server.

From step 402, the process proceeds to 404 in which the system configuration is determined. More specifically, system configuration is determined as a function of the location scenario (step 402). A system configuration may be stored in memory in
25 connection with each possible location scenario. Next, at step 406, default components are provided according to the determined system configuration. The default components include those components favorable for operation of the software system for the location scenario. By way of example, certain components and/or sub-components may be applicable to a software system installed at one of the location
30 scenarios, while other components and/or sub-components may be useful for all of the location scenarios. That is, the default components may be determined based on assumptions made in connection with how the software system should be configured when the software system is installed for a particular location scenario. A list of the

default components may be provided to the user *via* an appropriate GUI (*see, e.g.,* Fig. 7). A user may, in turn, customize the setup/installation, such as by deselecting one or more of the default components and/or selecting other components to be installed. The process then proceeds to step 408.

5 At step 408, component selections are received. For example, the component selections may correspond to an acceptance of all the default components and sub-components provided at step 406. Alternatively or additionally, the component selections may correspond to a customized component selection, which may include additional components and/or less than all the default components. A suitable user
10 interface element may be provided to submit the selected components for installation.

 Next, at step 410, component configuration is determined for the selected components and sub-components. In particular, certain components may be configured to provide desired functionality according to the selected location scenario for the installation. Such functionality may be implemented by providing different
15 sub-components in dependence upon the location scenario. As a result, the functionality of the selected components may be tuned as a function of the location scenario and configuration characteristics associated with the system installation.

 Next, the process proceeds to step 412 in which the selected components and sub-components there are installed. The installed components thus provide
20 functionality specific to the selected location scenario. In this way, the installation/setup process is facilitated both to the user and to the resulting software system that is installed. In particular, a user typically is clear as to where a software system is to be installed. Based on the selected location and certain assumptions about the configuration of a system at such a location the installation may be adapted
25 to provide the user with options and defaults tuned to the particular configuration being implemented. From step 412, the process proceeds to step 414 where the process may end.

 What has been described above includes exemplary implementations of the present invention. It is, of course, not possible to describe every conceivable
30 combination of components or methodologies for purposes of describing the present invention, but one of ordinary skill in the art will recognize that many further combinations and permutations of the present invention are possible. Accordingly,

the present invention is intended to embrace all such alterations, modifications and variations that fall within the spirit and scope of the appended claims.

Claims

What is claimed is:

1. A system for facilitating configuration of a software system being installed, comprising:
a setup component for receiving information indicative of a location scenario relating to where the software system is being installed, configuration characteristics for the software system being determined based on the location scenario.
2. The system of claim 1, wherein the software system further comprises a plurality of available components, the configuration characteristics further including default components selected for installation from the plurality of available components based on the location scenario.
3. The system of claim 2, further comprising a component selection user interface which is programmed to identify the default components and, in response to receiving a user input, to select which of the plurality of available components of the software system are to be installed, the operating characteristics for at least some of the selected components being controlled as a function of the location scenario.
4. The system of claim 1, wherein the setup component further comprises a location user interface component for presenting at least two location scenarios associated with installation of the software system, the location user interface component being operative to set the location scenario in response to receiving an associated user input.
5. The system of claim 1, further including computer-executable instructions associated with the setup component for accessing stored system information and determining configuration characteristics associated with a location onto where the software system is being installed, the location scenario being determined based on the configuration characteristics.

6. The system of claim 1, wherein the software system is a server system having a plurality of server components and the location scenario is selected from at least two scenarios including a central server scenario and a branch office server scenario.

7. A system for facilitating configuration of a software system being installed, comprising:

means for identifying a location scenario associated with a computer where the software system is to be installed; and

means for determining a configuration for the software system the based on the location scenario.

8. A method for configuring a software system, comprising:

selecting a scenario based on a location where the software system is to be installed; and

determining a configuration for the software system the based on the selected scenario.

9. The method of claim 8, wherein the software system includes a plurality of components, the step of determining further comprising determining at least one default component to install from the plurality of components based on the selected scenario.

10. The method of claim 9, further comprising providing a user interface which identifies the at least one default component.

11. The method of claim 10, further including selecting which of the plurality of components are to be installed and controlling operating characteristics of at least some of the selected components as a function of the selected scenario.

12. The method of claim 8, further comprising presenting at least two possible location scenarios via an associated user interface, the step of selecting further comprising selecting the scenario from one of presented scenarios.

13. The method of claim 8, wherein the step of selecting further comprises accessing stored system information and determining configuration characteristics associated with a location onto where the software system is being installed, the selected scenario being determined based on the determined configuration characteristics.

14. The method of claim 8, wherein the software system is a server system having a plurality of server components and the selected scenario is selected from at least two scenarios including a central server scenario and a branch office server scenario.

15. A computer-readable medium having computer-executable instructions for:

receiving data indicative of a location scenario where a software system is to be installed; and

configuring the software system based on the location scenario.

16. The computer-readable medium of claim 15, having further computer-executable instructions for determining at least one default component to install from a plurality of available components based on the location scenario.

17. The computer-readable medium of claim 16, having further computer-executable instructions for providing an interactive user interface that identifies the at least one default component.

18. The computer-readable medium of claim 17, having further computer-executable instructions for selecting which components of the software system are to be installed based on user input via the user interface and controlling operating characteristics of at least some of the selected components as a function of the location scenario.

19. The computer-readable medium of claim 15, having further computer-executable instructions for providing a user interface that presents at least two possible location scenarios and for receiving instructions via the user interface for selecting the location scenario from the presented scenarios.

20. The computer-readable medium of claim 19, wherein the software system is a server system having a plurality of server components, the computer-readable medium having further computer-executable instructions for presenting the at least two possible location scenarios to include a central server scenario and a branch office server scenario.

21. The computer-readable medium of claim 15, having further computer-executable instructions for accessing stored system information and determining configuration characteristics associated with a location onto where the software system is being installed, the location scenario being determined based on the determined configuration characteristics.

5




FIG. 1




FIG. 2

SERVER LOCATION

Select the location of the server. This will provide you with a recommended configuration that you can customize.


104 **CENTRAL SERVER**

This server will be used as part of the main infrastructure for my organization

106 **BRANCH OFFICE SERVER**

This server will be added to my organization's existing domain structure and configured to connect to the central server.

110
More Information



114

Cancel

Next >

< Back

112

100

FIG. 3


SERVER TYPE

Specify the type of server.

Do you want this server to be a domain controller or a member server?

- ☒ **152** First Domain Controller
- ☐ **154** Additional Domain Controller
- ☐ **156** Member Server

More Information



158

< Back

Next >

Cancel

150

FIG. 4

SERVER LOCATION

Select the location of the server. This will provide you with a recommended configuration that you can customize.

204

CENTRAL SERVER

This server will be used as part of the main infrastructure for my organization


206

BRANCH OFFICE SERVER

This server will be added to my organization's existing domain structure and configured to connect to the central server.

210

More Information



208

212

< Back

Next >

Cancel

214

FIG. 5

SERVER TYPE

Specify the type of server.

Do you want this server to be a member server or a domain controller?

☒ Member Server

☐ Additional Domain Controller

More Information

mydomain.com

< Back

Next >

Cancel

226

220

FIG. 6

COMPONENT SELECTION

Select the components you want to install.

ACTION

INSTALL

INSTALL

INSTALL

INSTALL

252

COMPONENT(S)

+ COMPONENT 1

+ COMPONENT 2

+ COMPONENT 3

SUBCOMPONENT 1

SUBCOMPONENT 2

+ COMPONENT 4

254

•

•

•

INSTALL

+ COMPONENT N

256

More Information

258

< Back

262

Next >

260

Cancel

250

FIG. 7




FIG. 8




FIG. 9

POWER OF ATTORNEY

As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (List name and registration number)

Himanshu S. Amin, Reg. No. 40,894; Gregory Turocy, Reg. No. 36, 952;
Christopher P. Harris, Reg. No. 43,660; Eric M. Highman,
Reg. No. 43,672; and Gary J. Pitzer, Reg. No. 39,334.

Katie E. Sako, Reg. No. 32,628 and Daniel D. Crouse, Reg. No. 32,022.

The undersigned to this declaration and power of attorney hereby authorizes the U.S. attorney(s) named herein to accept and follow instructions from:

Name(s) of authorized representative(s) _____
Address _____

as to any actions to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney(s) and the undersigned. In the event of a change in the person(s) from whom instructions may be taken, the U.S. attorney(s) will be so notified by the undersigned.

Send Correspondence To:

Himanshu S. Amin
AMIN, ESCHWEILER & TUROCY, LLP
24TH Floor, National City Center
1900 East 9TH Street
Cleveland, Ohio 44114

Direct Telephone Calls To:
(name and telephone number)

Himanshu S. Amin
(216) 696-8730

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued therein.

Full name of **sole or first inventor**, if any: Erin M. Bourke-Dunphy
Inventor's signature: [Signature]
Date: November 8th 2000 Country of Citizenship: Canada
Residence: Seattle, Washington
Post Office Address: 1455 E. Harrison Street, Apt. C12
Seattle, Washington 98112

Full name of **second or joint inventor**, if any: Jeff A. Zimmiewicz
Inventor's signature: [Signature]
Date: Nov 8th 2000 Country of Citizenship: U.S.
Residence: Bellevue, Washington
Post Office Address: 17035 NE 28th Place
Bellevue, Washington 98008

CHECK FOR ANY OF THE FOLLOWING ADDED PAGE(S) WHICH
FORM A PART OF THIS DECLARATION

X This declaration ends with this page.